

## Order Detail View - International 7300 SFA 4x4

## Sample Spec

Contact your local International dealer for spec compatibilities

**Order:**  
**Customer PO No:**  
**Order Date:** 7/15/2003  
**Sales Rep:**  
**Region:**  
**Model Code:** SR51500  
**SPA Nbr:**  
**Reference ID:** W.O.C.  
**Job:**  
**Current Step:** 21 : Fully Coded  
**GVWR:** 27000  
**WB:** 179  
**Build Estimate:**  
**Fleet Account:** 99999  
**Order Cust Info:** WORLD OF CONCRETE 7300 4X4  
**Application Code:** 532000  
**Dealer:** 000000- 000

**Order Qty:** 1  
**Ship Rqst Date:**  
**Country of Use:** UNITED STATES  
**Plant:** GARLAND ASSEMBLY PLANT  
**Model Desc:** 7300 SFA 4X4  
**Prior Order Content:** 9/20/2003  
**Policy Announcement No:**  
**Chassis:**  
**VIN:**  
**Paint:** 100GM S 6J05  
**AF:** 49  
**Delivery Date:**  
**Fleet Cust Name:**

**Qty to Produce:** 1  
**Ordered By:**  
**Market:** UNITED STATES  
**Customer Vehicle ID:**  
**Gear Ratio:** 5.29  
**Assembly Line No:** 1

**Application Description:** Construction Dump  
**GOODS LOANED-TRUCK**  
**P O BOX 1488**  
**WARRENVILLE ,IL 60555**

Unit	Description
0001CAD	FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm); 420.0" (10668mm) Maximum OAL
0001LMY	BUMPER, FRONT Full Width, Aerodynamic, Chrome Plated Steel; 0.189" Material Thickness
0001WGE	WHEELBASE RANGE 148" (375cm) Through and Including 179" (455cm)
0001570	TOW HOOK, FRONT (2) Frame Mounted.
0002ESC	AXLE, FRONT DRIVING TYPE Meritor MX-10-120 Single Reduction, 10,000-lb Capacity
0002WLA	AXLE, FRONT DRIVING, LUBE EmGard 75W-90 Synthetic Oil; 1 thru 29.99 Pints
0003ADB	SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 10,000-lb Capacity; With Shock Absorbers
0004AZA	AIR BRAKE ABS Bendix AntiLock Brake System Full Vehicle Wheel Control System (4-Channel)
0004JBL	BRAKES, FRONT, AIR CAM S-Cam; 16.5" x 5.0"; Includes 20 Sq. In. MGM Long Stroke Brake Chambers

0004NCE BRAKES, REAR, AIR CAM 16.5" x 7.0"; Includes MGM TR3030 Long Stroke Brake Chamber and Heavy Duty Spring Actuated Parking Brake  
 0004SBC AIR COMPRESSOR Bendix Tu-Flo 550 13.2 CFM  
 0004091 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications  
 0004732 DRAIN VALVE Berg for Air Tank Manual; With Pull Chain,  
 0005CAN STEERING WHEEL 2-Spoke; 18" Diam., Black, Leather Wrapped  
 0005PSA STEERING GEAR Sheppard M-100 Power  
 0005708 STEERING COLUMN Tilting  
 0270DYA1124 PROPSHAFT  
 0414STH1525 PROPSHAFT  
 0414STH1600 PROPSHAFT  
 0007BAW EXHAUST SYSTEM Frame Mounted Right Side with Under Cab Muffler Single, Horizontal Muffler; Vertical Bright Finish Tail Pipe; Includes Bright Finish Tail Pipe Guard;  
 0008GCH ALTERNATOR Delco-Remy America Inc. 33-SI 12-Volt 110 Amp. Capacity, Brushless  
 0008HAA BODY BUILDER WIRING To Rear of Frame, With Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket  
 0008MEP BATTERY SYSTEM International Maintenance-Free (2) 12-Volt 1300CCA Total.  
 0008RDU RADIO Panasonic CQ-5400U AM/FM Premium Stereo, With CD Player, Weatherband, Clock With Alarm, CD Changer Interface and Controls, Auxiliary Input Jack, With Multiple Coaxial Speakers  
 0008WBW JUMP START STUD Remote Mounted.  
 0008WCL HORN, AIR Grover Mounted Behind Bumper on Right Rail Black, Single Trumpet, Air Solenoid Operated,  
 0008WLM FOG LIGHTS Peterson (2) Amber, Halogen, Rectangular  
 0008WML HEADLIGHTS Long Life Halogen; for Two Light System  
 0008WPH CLEARANCE/MARKER LIGHTS Truck Lite (5) Amber LED Lights, Flush Mounted on Cab or Sunshade  
 0008WPK COURTESY LIGHT (4) Two Front Mounted Under Instrument Panel and Two for Rear Doors, (One each Side)  
 0008WWJ INDICATOR, LOW COOLANT LEVEL With Audible Alarm  
 0008WWW STARTING MOTOR Leece-Neville MS2 ILO M100R 12-Volt; less Thermal Over-Crank Protection, for Temporary Vendor Substitution Only, NOT an Orderable Code  
 0008XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses  
 0008000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment  
 0008518 CIGAR LIGHTER  
 0008540 HORN, ELECTRIC (2)  
 0009HAD GRILLE Chrome  
 0009WAY FRONT END Tilting, Fiberglass, With Three Piece Construction  
 0009579 FENDER EXTENSIONS Injection Molded TPO  
 0010WZD COMPETITIVE SURCHARGE CREDIT  
 0010060 PAINT SCHEMATIC, PT-1 Single Color, Design 100  
 0010761 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone  
 0010769 PAINT CLASS Premium Color.  
 0011001 CLUTCH Omit Item (Clutch & Control)  
 0012NNG ENGINE, DIESEL International DT466 Standard Torque Electro-Hydraulic Fuel System, 50 State, 215 HP @ 2300/2600 RPM, 540 lb-ft Torque @ 1400 RPM, 2600 RPM Governed Speed, 215 Peak HP (Max)  
 0012TSY FAN DRIVE Borg-Warner SA85 Viscous Screw On Type  
 0012UVX RADIATOR Cross Flow, Series System; 940 Sqn Aluminum Radiator Core With Internal Water to Oil Transmission Cooler and 1025 Sqn Charge Air Cooler  
 0012UXC FEDERAL EMISSIONS for 2002; for International VT365, T444E, DT466 and DT530 Engines  
 0012VBB AIR CLEANER Dual Element  
 0012VXT THROTTLE, HAND CONTROL Mounted on Steering Wheel Engine Speed Control; Electronic, Stationary, Variable Speed;  
 0013ACS TRANSMISSION, AUTOMATIC ALLISON 2000P SERIES 5-Speed, With Overdrive, With PTO Gear, Less Retarder  
 0013TKC TRANSFER CASE Meritor MTC-4208 2-Spd, 8,300 lb-ft Total Capacity, With Provision for PTO, With

Electric Over Air Control  
 0013WDB TRANSFER CASE LUBE EmGard 50W Synthetic; 1 thru 14.99 Pints  
 0013WLE TRANSMISSION OIL Castrol TranSynd Synthetic; 20 thru 28 Pints  
 0014ATB AXLE, REAR, SINGLE Meritor RS-17-145 Single Reduction, Standard Track, 17,000-lb Capacity, With 190 Wheel Ends  
 0014SAH SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 18,500-lb Capacity  
 0015SGG FUEL TANK Mounted Left Side, Under Cab Top Draw; D Style, Non Polished Aluminum, 19" Deep, 70 U.S. Gal., 265 L Capacity, With Quick Connect Outlet,  
 0016HBA GAUGE CLUSTER English With English Electronic Speedometer  
 0016HGH GAUGE, OIL TEMP, ALLISON TRAN  
 0016JNV SEAT, DRIVER National Air Suspension, High Back With Integral Headrest, Cloth, Isolated, With 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Air Lumbar Support  
 0016RPX SEAT, PASSENGER National Air-Suspension, High Back With Integral Headrest, Cloth, Isolated, With 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Air Lumbar Support  
 0016RZJ SEAT, REAR BENCH International Full Width; Cloth, With Fixed Back and Two Integral Outboard Headrest  
 0016SDU MIRRORS Lang Mekra (2) LED, Powered Both Sides, Bright Heads & Brackets Styled; Rectangular, 7.09" x 15.75", Brackets Breakaway Type, With 102" Wide Spacing, With Integral Convex Both Sides, With All Heated Heads, Thermostatically Controlled, With Clearance Lights  
 0016WBY ARM REST, RIGHT, DRIVER SEAT  
 0016WBZ ARM REST, LEFT, PASSENGER SEAT  
 0016WEE CAB SOUND INSULATION Includes Dash Insulator and Engine Cover Insulator  
 0016WJT INSTRUMENT PANEL Center Section, Ergonomic Panel  
 0016WJV WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right  
 0016WKB AIR CONDITIONER International Blend-Air With Integral Heater & Defroster  
 0016WKY FRESH AIR FILTER for HVAC  
 0016WKZ KEYLESS ENTRY SYSTEM REMOTE With Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)  
 0016WLE STORAGE POCKET, DOOR Mounted on Passenger Door Molded Plastic, Smoke Gray, Full Width;  
 0016WSG CAB INTERIOR TRIM Deluxe; for Crew Cab  
 0016WSK CAB REAR SUSPENSION Air Bag Type  
 0016196 CAB Conventional Steel; 6-Man Crew Cab  
 0027DMC WHEELS, FRONT DISC; 22.5" Polished Aluminum, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs  
 07302690179 TIRE, FRONT (2) 11R22.5 UNISTEEL G159 GOODYEAR 501 REV/MILE G14PLY  
 0028DMC WHEELS, REAR DUAL DISC; 22.5" Polished Aluminum, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs.  
 07302690182 TIRE, REAR (4) 11R22.5 UNISTEEL G167A GOODYEAR 497 REV/MILE G14PLY

0060EGD Integrated Pick-up Truck

Electronic Parameter	Parameter Data
<b>CUSTOMER PASSWORD</b>	<b>0000</b>
<b>MAX SPEED</b>	<b>80 MPH</b>
<b>MIN CRUISE SPEED</b>	<b>35 MPH</b>
<b>MAX CRUISE SPEED</b>	<b>80 MPH</b>
<b>RETARDER - SERVICE BRAKE INTERFACE</b>	<b>0</b>
<b>MAX PTO ENGINE SPEED</b>	<b>2600 RPM</b>
<b>SET ENGINE SPEED (speed 1)</b>	<b>1000 RPM</b>
<b>RESUME ENGINE SPEED (speed 2)</b>	<b>1200 RPM</b>
<b>DISABLE CAB INTERFACE FOR PTO</b>	<b>0</b>
<b>REMOTE THROTTLE FOR PTO CONTROL</b>	<b>0</b>
<b>ENGINE RESPONSE RATE FOR PTO</b>	<b>250 RPM</b>
<b>ENGINE RESPONSE RATE FOR PTO</b>	<b>250 RPM/SEC</b>
<b>MAX ROAD SPEED FOR MOBILE CONTROL</b>	<b>20 MPH</b>
<b>IDLE SHUTDOWN MODE</b>	<b>0</b>
<b>SERVICE INTERVAL</b>	<b>0</b>